


#### COMPONENTS LIST



1. Install ECU, OBD and wiring



1) take out fuse



2) connect power wire to battery: red one with fuse is positive.



3) CAUTION!: Tighten battery screw very tight! If loose, may get damage to the car



4)The left motor line from above position to the leaf plate



5)The left motor line as above to the chassis and connect with motor



6) The right motor	line	goes	to	the
right				



7) the right motor line pass through here to the chassis. Same as left.



8) three lines from above position to co-drive position: positive line, another terminal of left and right motor line.



9) another terminal line of left and right motor line as above picture.



10) insert those 3 lines connector and with tape protected. **Connector inside th car to anti the water**!



11) The negative connect above position to get power.




12) The ECU is fixed as above




13) Plug in the OBD connector

14) Connect motor connectors and use tape to protect, connect OBD line with ECU connector, insert fuse to test if motor work well




**KEEPALL SCREWS A LITTLE LOOSE, SO THAT BRACKET CAN MOVE WITH RUNNING BOARD!!!** 



KEEPALL SCREWS A LITTLE LOOSE, SO THAT BRACKET CAN MOVE WITH RUNNING BOARD!!!


4. install running board (left and right side are in same way)



#### 5. <u>Testing and adjust the balance</u>



Insert fuse again. Then open and close doors to let step work. To assure them up and down freely to adjust position by itself.



6. Checking all doors activate, the side step work when doors open and close.






Now the installation is finished. Protect all connectors with tap to avoid loose.



To lift the car as showed



To lift the car  $% \left( {{{\left( {{{\left( {{{\left( {{{\left( {{{c}}} \right)}} \right.}$ 



To changing tire

#### Automatic power deploy:

The running boards will extend down and out when the door is opened.

#### Automatic stop:

If an object is in the way of the moving running board, the running board will automatically stop. To reset, clear any obstruction, then simply open and close the door to resume normal operation.

#### Manually set in the deployed (OUT) position for access to the roof:

Step your foot while at the same time closing the door. To resume normal operation, open and close the door.

**Maintenance:** In adverse conditions, debris such as mud, dirt, and salt may become trapped in the running board mechanism, possibly leading to unwanted noise. If this occurs, manually set the running boards to avoid spraying the motors directly. After washing, apply silicone spray lubricant to the hinge pivot pins.

**Caution!** Keep hands and feet away when the running board is in motion.